



44018series – 44030series

Heavy Duty 4-Post Surface Mounted Lifts

PANZITTA SALES & SERVICE
 72 George Avenue
 Wilkes-Barre, PA 18705
 570-822-6720 800-822-6720
 www.panzittasales.com



44018 Features:

- Superior lifting system features tensile lift chain and sealed roller bearings for maximum reliability
- Heavy-duty cylinder provides optimum lifting with minimum maintenance
- AR models feature double radius gauge cut outs, dual rear slip plates, internal airline kit, and single point air actuated lock release with 17 level working alignment heights

44030 Features:

- Superior lifting system features tensile lift chain and sealed roller bearings for maximum reliability
- Heavy-duty cylinder provides optimum lifting with minimum maintenance
- Single point air actuated lock release
- AR models feature turning radius gauge cut outs and optional flush mounted 10500HD gauges



44018 accessories:

Part #	Description
SAJ9S	Air Hydraulic rolling jack for 44018 and 44018E
SAJ9A	Air Hydraulic rolling jack for 44018AR
10500	Powder coat turning radius gauges
10500SS	Stainless Steel turning radius gauges
44RK18	Ramp kit, pivoting, 39" long
44RKE18	Ramp kit, pivoting, 52" long for AR's only
10267	Oil drain pan kit, adj. width, 32 gallon

44030 accessories:

Part #	Description
SAJ15	15,000 lbs. rolling jack adj. width 36" - 52"
10267	Oil drain pan kit, adj. width, 32 gallon
10500HD	HD powder coated turning radius gauges
44RK30	Ramp kit, pivoting, 36" long for drive thru
44RKE30	Ramp kit, pivoting, 72" long for drive thru



Part#: SAJ15

- 15,000 lbs. lifting capacity
- Adjustable width 36" - 52"

Model Number	44018	44018E	44018AR	44030	44030AR	44030E	44030EAR	44030X	44030XAR
Lift Capacity	18,000 lb.	18,000 lb.	18,000 lb.	30,000 lb.	30,000 lb.	30,000 lb.	30,000 lb.	30,000 lb.	30,000 lb.
Maximum Wheelbase	194"	230"	236"	230"	230"	290"	290"	350"	350"
Min.-Max.-4 Wheel Align	N/A		98" - 206"	N/A		N/A		N/A	
Max. 2 Wheel Alignment	N/A		220"	N/A	206"	N/A	266"	N/A	326"
Rise	78¾"		83¾"	68"		68"		68"	
Overall Length	21' 4"	24' 4"	25' 11½"	24' 7½"		29' 7½"		34' 7½"	
Overall Width	11' 6⅛"		11' 9½"	12' 5½"		12' 5½"		12' 5½"	
Overall Height	8' 6½"			92"		92"		92"	
Inside of Columns	121"		122"	132½"		132½"		132½"	
Between Columns	204"	240"	204"	233¾"		293¾"		353¾"	
Width of Runways	22"			24"		24"		24"	
Height of Runways	7¼"		11⅞"	9"		9"		9"	
Width Between Runways	36" - 54"			54" - 75"		54" - 75"		54" - 75"	
Motor	3HP			3HP		3HP		3HP	
Voltage - Single Phase	208 - 230v			208-230v		208-230v		208-230v	
Speed of Rise	60 sec.			105 sec.		105 sec.		105 sec.	
Amps	30			30		30		30	